




Cod.	 Angle	 bar	 l/min	l/ha (spaziatura tra gli ugelli: 50 cm)						ISO	
				l/ha (nozzle spacing: 50 cm)							
				6 km/h	8 km/h	10 km/h	12 km/h	14 km/h	16 km/h	18 km/h	
422DEF01	--	1	0.23	46	35	28	23	20	17	15	✓
	--	2	0.33	65	49	39	33	28	24	22	
	120°	3	0.40	80	60	48	40	34	30	27	
422DEF015	--	1	0.35	69	52	42	35	30	26	23	✓
	--	2	0.49	98	73	59	49	42	37	33	
	120°	3	0.60	120	90	72	60	51	45	40	
422DEF02	--	1	0.46	92	69	55	46	40	35	31	✓
	--	2	0.65	131	98	78	65	56	49	44	
	110°	3	0.80	160	120	96	80	69	60	53	
422DEF025	--	1	0.58	115	87	69	58	49	43	38	✓
	--	2	0.82	163	122	98	82	70	61	54	
	95°	3	1.00	200	150	120	100	86	75	67	
422DEF03	--	1	0.69	139	104	83	69	59	52	46	✓
	--	2	0.98	196	147	118	98	84	73	65	
	100°	3	1.20	240	180	144	120	103	90	80	
422DEF04	--	1	0.92	185	139	111	92	79	69	62	✓
	--	2	1.31	261	196	157	131	112	98	87	
	120°	3	1.60	320	240	192	160	137	120	107	
422DEF05	--	1	1.15	231	173	139	115	99	87	77	✓
	--	2	1.63	327	245	196	163	140	122	109	
	120°	3	2.00	400	300	240	200	171	150	133	
422DEF06	--	1	1.39	277	208	166	139	119	104	92	✓
	--	2	1.96	392	294	235	196	168	147	131	
	120°	3	2.40	480	360	288	240	206	180	160	
422DEF08	--	1	1.85	370	277	222	185	158	139	123	✓
	--	2	2.61	523	392	314	261	224	196	174	
	120°	3	3.20	640	480	384	320	274	240	213	
422DEF105	--	1	2.43	486	365	292	243	208	182	162	✗
	--	2	3.44	687	516	412	344	295	258	229	
	135°	3	4.21	842	632	505	421	361	316	281	